

# JUKI

LOWEST COST OF OWNERSHIP

## Incoming Material Station



Industry 4.0  
ready



Time saving



Reduce human  
mistake



Delivery note  
matching




Part Number  
Control



1D/2D codes  
auto detect



Connected to  
ISM towers



Storage solutions.it<sup>®</sup>  
division

# Incoming Material Station

Hardware	Included by default	Software	Included by default	Software Options	Included by default
ESD table	✓	Software Console	✓	Part number control	OPTION
Touch screen, keyboard, mouse	✓	Halcon 1D-2D library	✓	Delivery note matching	OPTION
18 mp camera	✓	Auto-Incoming software	✓		
Label printer	✓	Picture traceability option	✓		
1D/2D barcode scanner	✓				
PC i7, 8GB RAM 256 GB	✓				

TECHNICAL DATA	
<b>Dimensions:</b>	Width = 1,6 m / 5.25 ft Depth = 0,8 m / 2.62 ft
<b>Operating Height:</b>	1,1 m (3.28 ft)
<b>Weight:</b>	101 Kg - 222.67 Kg (Full cases)
<b>Power consumption:</b>	100-240V - Imax: 5A - Frequency: 50-60 Hz
<b>Operating system:</b>	Microsoft Win 10;



trays storage

## Features and Benefits

Through the Incoming Material Station operators will speed up material registration activities, avoid mistakes, and increase the traceability of each individual Unique ID.

With its Auto-Incoming features, it is possible to automatically import information from the supplier and/or customer's label into the ERP, and print a new Unique ID. In fact, after setting the rules for each supplier's label, the operator can simply position the material on the Station and the high resolution camera will read all the needed codes and information, take a picture for traceability purposes and print the new label.

Moreover, through the included "Reels Pictures Traceability" feature all pictures will be stored inside the database and can be recalled for any future visualization and quality check. While this tool brings traceability to a higher level of quality standard, it can also provide evidence of damaged or mislabelled material coming from the suppliers.

The table, with its robust folded metal structure, is studied to guarantee an adequate load support, along with the demanding standards of an electronic production environment, with the top ESD shelf, made of static dissipative laminate, with 10M Ohm resistivity and a protective black PVC contour.

### Requirements

The Incoming Material Station should be connected to an existing installation where the ISM SMT or THT Server software is operating.

### Interfacing

The connection with other systems (ERP, MES, Pick and Place, etc) is possible thanks to the API interface that allows any software to communicate and receive information from the Incoming Material Station. Automatic file sharing with other software is also possible.

### Auto-Detect

The camera and software are able to recognize, parse and store any 1D/2D code on the top of the reels. The software is set with standard rules\* used by most components suppliers to label their products (available field: Part number, Unique ID, Case format, Quantity, Bin, Date code, MSL, Manufacture PN, Lot number, Expiring date, Supplier, Order ref., Notes field, custom field).

Any out-of-standard label can be easily read by setting customized rules as long as the codes contain a recognizable indicator (for example: Q2000, "Q" standing for quantity).

\*It is possible to access the documentation used to create the standard rules by contacting our local distributor.





**JUKI**



Storage**solutions.it**  
division

**North America Headquarters:**

Juki Automation Systems  
5151 McCrimmon Parkway  
Suite 200  
Morrisville, NC 27560  
Phone: 919-460-0111  
Email: [sales@jas-smt.com](mailto:sales@jas-smt.com)

**North America Sales Office:**

Juki Automation Systems  
412 Kato Terrace  
Fremont, CA 94539  
Phone: 510-249-6700

**[www.jukiamericas.com](http://www.jukiamericas.com)**

JUKI Specifications and appearance may be changed without notice.  
This catalogue prints with environment-friendly soyink on recycled paper.